



## 38 S&W

.357"	38 JHP	38 GDHP SB
Weight (grains)	110	110
Ballistic Coefficient	0.113	0.117
Sectional Density	0.123	0.123
COAL Tested	1.055"	1.055"
Speer Part No.	4007	4009

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Alliant Herco	Winchester	CCI 500	5.0	1013	5.3	1060
Alliant Unique	Winchester	CCI 500	4.8	938	5.1	1001
Alliant Bullseye	Winchester	CCI 500	3.0	894	3.2	935
Alliant Red Dot	Winchester	CCI 500	3.2	852	3.5	929
IMR SR 7625	Winchester	CCI 500	3.5	826	3.8	909
Winchester 231	Winchester	CCI 500	2.9	725	3.2	797

**WARNING:** Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

*Maximum loads should be used with CAUTION • C = Compressed Load*