



38 Special +P

0.358"	35 LSWC	35 LSWC HP	35 LRN
Weight (grains)	158	158	158
Ballistic Coefficient	0.123	0.121	0.170
Sectional Density	0.176	0.176	0.176
COAL Tested	1.440"	1.455"	1.510"
Speer Part No.	4624	4628	4648

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Alliant Power Pistol	Speer	CCI 500	5.4	948	6.0	1037
Hodgdon Hi-Skor 700-X	Speer	CCI 500	3.8	877	4.4	980
Accurate No. 5	Speer	CCI 500	6.2	922	6.6	978
Hodgdon HS-6	Speer	CCI 500	6.3	914	6.7	971
Hodgdon H. Universal	Speer	CCI 500	4.6	902	5.0	971
IMR PB	Speer	CCI 500	4.2	858	4.6	962
Winchester 231	Speer	CCI 500	4.3	863	4.7	935
Alliant Unique	Speer	CCI 500	4.7	815	5.2	919
Hodgdon HP-38	Speer	CCI 500	4.1	855	4.5	918
Vihtavuori N350	Speer	CCI 500	5.0	818	5.4	901
Winchester WSF	Speer	CCI 500	4.3	830	4.7	892
Alliant Bullseye	Speer	CCI 500	3.5	814	3.9	874
Alliant Red Dot	Speer	CCI 500	3.4	793	3.8	846
Accurate No. 2 Improved	Speer	CCI 500	4.0	781	4.3	843

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load