



44 Smith & Wesson Special

.430"	44
Weight (grains)	LSWC
Ballistic Coefficient	240
Sectional Density	0.151
COAL Tested	0.185
Speer Part No.	1.475"
	4661

NOTE: Velocities determined using a Taurus revolver with 3" barrel.

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Alliant Unique	Remington	CCI 300	5.7	746	6.3	820
Alliant Herco	Remington	CCI 300	5.8	730	6.4	816
Hodgdon HS-6	Remington	CCI 350	7.0	695	8.0	815
Winchester 231	Remington	CCI 300	5.2	701	5.7	796
Alliant Bullseye	Remington	CCI 300	4.7	691	5.2	793
Alliant Red Dot	Remington	CCI 300	4.5	658	5.0	750
Alliant Green Dot	Remington	CCI 300	5.2	672	5.7	749
Hodgdon Hi-Skor 700-X	Remington	CCI 300	4.1	640	4.6	734

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load