



45 G.A.P.

.451"	45
Weight (grains)	GDHP
Ballistic Coefficient	200
Sectional Density	0.138
COAL Tested	0.140
Speer Part No.	1.070"
	4478

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Alliant Unique	Speer	CCI 500	6.3	918	6.8	988
Hodgdon H. Universal	Speer	CCI 500	5.8	893	6.2	988
Alliant Power Pistol	Speer	CCI 500	6.9	903	7.6	977
Alliant Bullseye	Speer	CCI 500	4.9	859	5.4	943
Hodgdon TITEGROUP	Speer	CCI 500	4.6	865	5.1	940
Accurate No. 5	Speer	CCI 500	7.3	848	8.0	921
Ramshot True Blue	Speer	CCI 500	6.8	851	7.4	912
Winchester 231	Speer	CCI 500	5.0	840	5.5	900
Vihtavuori 3N37	Speer	CCI 500	6.8	811	7.2	863
Accurate No. 2 Improved	Speer	CCI 500	4.3	783	4.7	838

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load