



475 Linebaugh

<b>.475"</b>	<b>475</b>
<b>Weight (grains)</b>	<b>DCSP</b>
<b>Ballistic Coefficient</b>	325
<b>Sectional Density</b>	0.191
<b>COAL Tested</b>	0.206
<b>Speer Part No.</b>	1.750"
	3978

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
<b>Accurate No. 9</b>	Buffalo Bore	CCI 350	26.0	1324	<b>28.0</b>	1429
<b>Vihtavuori N110</b>	Buffalo Bore	CCI 350	25.5	1308	<b>27.5</b>	1412
<b>Alliant 2400</b>	Buffalo Bore	CCI 350	25.0	1262	<b>27.0</b>	1371
<b>Accurate No. 7</b>	Buffalo Bore	CCI 350	19.0	1153	<b>23.0</b>	1363
<b>Alliant Blue Dot</b>	Buffalo Bore	CCI 350	18.0	1159	<b>20.0</b>	1324
<b>Alliant Power Pistol</b>	Buffalo Bore	CCI 350	15.5	1168	<b>17.5</b>	1302
<b>Alliant Unique</b>	Buffalo Bore	CCI 350	13.5	1107	<b>15.5</b>	1221
<b>Vihtavuori N350</b>	Buffalo Bore	CCI 350	14.5	1065	<b>16.5</b>	1220

**WARNING:** Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

*Maximum loads should be used with CAUTION • C = Compressed Load*