



204 Ruger

.204"	20
Weight (grains)	TNT® HP
Ballistic Coefficient	39
Sectional Density	0.202
COAL Tested	0.134
Speer Part No.	2.260"
	1015

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Alliant Power Pro 2000-MR	Federal	CCI 400	26.9	3495	29.9	3804
Alliant AR-Comp	Federal	CCI 400	24.0	3559	26.2	3764
Alliant Reloder 15	Federal	CCI 400	25.6	3466	28.2	3756
Hodgdon CFE 223	Federal	CCI 400	24.9	3443	27.5	3745
IMR 8208 XBR	Federal	CCI 400	23.8	3463	26.2	3735
Alliant Power Pro Varmint	Federal	CCI 400	23.7	3393	26.4	3718
Ramshot X-Terminator	Federal	CCI 400	23.5	3424	25.8	3710
Vihtavuori N140	Federal	CCI 400	24.8	3435	27.4	3688
Accurate 2230	Federal	CCI 400	22.8	3421	24.9	3676
Vihtavuori N530	Federal	CCI 400	22.5	3435	24.3	3668
Alliant Power Pro 1200-R	Federal	CCI 400	21.5	3425	23.7	3665

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load