



## 22-250 Remington

<b>.224"</b>	<b>22</b>
<b>Weight (grains)</b>	<b>Spire SP</b>
<b>Ballistic Coefficient</b>	40
<b>Sectional Density</b>	0.144
<b>COAL Tested</b>	0.114
<b>Speer Part No.</b>	2.235"
	1017

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Alliant AR-Comp	Federal	Federal 210	33.1	3880	36.7	4228
IMR 8208 XBR	Federal	Federal 210	32.5	3873	36.1	4182
Alliant Reloder 10X	Remington	CCI 200	31.5	3780	35.5	4164
Ramshot X-Terminator	Federal	Federal 210	31.3	3805	34.8	4142
Alliant Power Pro 1200-R	Federal	Federal 210	29.5	3881	32.2	4108
Hodgdon Varget	Remington	CCI 200	35.0	3582	39.0	4090
Accurate 2460	Remington	CCI 250	34.0	3468	38.0	4033
Vihtavuori N130	Federal	Federal 210	28.5	3771	31.7	4033
Alliant Reloder 15	Remington	CCI 200	36.0	3443	40.0	4027
Hodgdon H4895	Remington	CCI 200	34.0	3542	38.0	4025
Vihtavuori N135	Remington	CCI 200	33.0	3463	37.0	3958
IMR 4320	Remington	CCI 200	36.0	3360	40.0	3930
Accurate 2520	Remington	CCI 250	33.0	3382	37.0	3910
Winchester 748	Remington	CCI 250	35.5	3403	39.5	3867
Winchester 760	Remington	CCI 250	38.0	3342	42.0	3841
IMR 4064	Remington	CCI 200	34.0	3390	38.0	3830
Hodgdon H380	Remington	CCI 250	39.0	3284	43.0 C	3796
Hodgdon H335	Remington	CCI 250	33.0	3280	37.0	3748
IMR 3031	Remington	CCI 200	32.0	3315	36.0	3746
IMR SR 4759 (reduced load)	Remington	CCI 200	9.0	1641	11.0	1979

**WARNING:** Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load