



220 Swift

.224"	22 HP	22 Match BTHP
Weight (grains)	52	52
Ballistic Coefficient	0.168	0.230
Sectional Density	0.148	0.148
COAL Tested	2.680"	2.680"
Speer Part No.	1035	1036

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Alliant Reloder 17	Hornady	CCI 200	37.9	3473	42.1	3886
Alliant Reloder 16	Hornady	CCI 200	39.6	3571	43.5 C	3881
Alliant Power Pro 4000-MR	Hornady	CCI 200	40.4	3499	44.4 C	3863
Alliant Power Pro 2000-MR	Hornady	CCI 200	35.6	3557	39.6	3816
IMR 4451	Hornady	CCI 200	38.6	3401	42.7	3772
Vihtavuori N160	Winchester	CCI 200	42.0	3372	46.0 C	3765
Alliant AR-Comp	Hornady	CCI 200	32.1	3492	35.6	3743
Alliant Reloder 15	Winchester	CCI 200	35.5	3295	39.5	3668
Accurate 4350	Winchester	CCI 200	41.0	3240	45.0 C	3663
Alliant Reloder 19	Winchester	CCI 200	42.0	3267	46.0 C	3642
Vihtavuori N140	Winchester	CCI 200	35.0	3268	39.0	3639
Hodgdon H380	Winchester	CCI 250	39.5	3328	43.5	3637
IMR 4350	Winchester	CCI 200	39.0	3199	43.0	3616
Winchester 760	Winchester	CCI 250	37.5	3212	41.5	3577
IMR 4831	Winchester	CCI 200	40.0	3028	44.0 C	3509
IMR 3031	Winchester	CCI 200	32.5	3200	36.5	3509
Hodgdon H4831	Winchester	CCI 200	41.0	3086	45.0 C	3492
IMR SR 4759 (reduced load)	Winchester	CCI 200	11.0	1679	13.0	1991

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load