



## 222 Remington Magnum

<b>.224"</b>	<b>22</b>
	<b>Spitzer SP</b>
<b>Weight (grains)</b>	45
<b>Ballistic Coefficient</b>	0.143
<b>Sectional Density</b>	0.128
<b>COAL Tested</b>	2.220"
<b>Speer Part No.</b>	1023

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Hodgdon H335	Remington	CCI 450	27.0	3397	<b>29.0</b>	3670
Winchester 748	Remington	CCI 450	28.0	3396	<b>30.0</b>	3662
IMR 4320	Remington	CCI 400	27.0	3339	<b>29.0</b>	3569
IMR 3031	Remington	CCI 400	25.0	3276	<b>27.0</b>	3532
IMR 4198	Remington	CCI 400	21.5	3203	<b>23.5</b>	3496
IMR 4895	Remington	CCI 400	25.0	3167	<b>27.0</b>	3403
Alliant Reloder® 7	Remington	CCI 400	21.5	3083	<b>23.5</b>	3355
IMR SR 4759 (reduced load)	Remington	CCI 400	8.5	1607	<b>10.5</b>	1987

**WARNING:** Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

*Maximum loads should be used with CAUTION • C = Compressed Load*