



223 Remington

.224"	22
	GD
Weight (grains)	75
Ballistic Coefficient	0.411
Sectional Density	0.214
COAL Tested	2.230"
Speer Part No.	22475GDB

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Alliant Power Pro 2000-MR	Federal	Federal 205	23.5	2655	26.1 C	2897
Hodgdon CFE 223	Federal	Federal 205	22.0	2583	24.0	2782
IMR 4895	Federal	Federal 205	21.2	2508	23.5 C	2767
Alliant Reloder 15	Federal	Federal 205	21.2	2514	23.6 C	2761
Ramshot X-Terminator	Federal	Federal 205	20.7	2544	22.9	2757
Alliant Power Pro Varmint	Federal	Federal 205	20.8	2533	23.0	2756
Accurate 2460	Federal	Federal 205	21.0	2524	23.2	2746
Hodgdon Varget	Federal	Federal 205	20.9	2515	23.2 C	2740
Vihtavuori N540	Federal	Federal 205	21.2	2462	23.5 C	2725
IMR 8208 XBR	Federal	Federal 205	20.0	2508	22.1	2723
Alliant AR-Comp	Federal	Federal 205	18.9	2480	20.9	2669
Hodgdon H335	Federal	Federal 205	19.0	2470	21.0	2638

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load