



223 Remington

.224"	22 TNT Green®
Weight (grains)	43
Ballistic Coefficient	0.150
Sectional Density	0.122
COAL Tested	2.150"
Speer Part No.	1022

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Alliant AR-Comp	Federal	Federal 205	23.0	3310	25.6	3561
Accurate 2230	Federal	Federal 205	23.1	3287	25.5	3545
Winchester 748	Federal	Federal 205	25.5	3334	27.5 C	3538
Alliant Power Pro Varmint	Federal	Federal 205	24.6	3338	26.8	3531
Hodgdon Varget	Federal	Federal 205	24.7	3232	27.3 C	3531
Hodgdon H335	Federal	Federal 205	23.1	3291	25.4	3511
Ramshot TAC	Federal	Federal 205	24.0	3291	26.0	3505
Alliant Power Pro 1200-R	Federal	Federal 205	21.5	3214	23.9	3490
Vihtavuori N540	Federal	Federal 205	25.5	3246	27.5 C	3481
Hodgdon H322	Federal	Federal 205	21.9	3231	24.3	3476
Alliant Reloder 10X	Federal	Federal 205	21.0	3179	23.0	3468
IMR 4895	Federal	Federal 205	23.7	3120	26.3 C	3433
Alliant Reloder 7	Federal	Federal 205	19.4	3115	21.5	3397
IMR 4198	Federal	Federal 205	17.9	3069	19.9	3381
Vihtavouri N130	Federal	Federal 205	19.4	3164	21.1	3353
Accurate 2015	Federal	Federal 205	21.2	3089	23.4	3340

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load