



22 PPC

.224"	22	22
	HP	Match BTHP
Weight (grains)	52	52
Ballistic Coefficient	0.168	0.230
Sectional Density	0.148	0.148
COAL Tested	2.040"	2.050"
Speer Part No.	1035	1036

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Hodgdon BL-C(2)	Sako	CCI BR4	26.5	3277	28.5 C	3550
Hodgdon H335	Sako	CCI BR4	26.0	3230	28.0 C	3491
Hodgdon H322	Sako	CCI BR4	25.0	3155	27.0 C	3393
Alliant Reloder 7	Sako	CCI BR4	22.0	3064	24.0	3327
IMR 4198	Sako	CCI BR4	21.5	3053	23.5	3323
Winchester 748	Sako	CCI BR4	28.0	3082	30.0 C	3321
IMR 4895	Sako	CCI BR4	25.0	3010	27.0 C	3237
IMR 3031	Sako	CCI BR4	24.0	2993	26.0 C	3221

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load