



240 Weatherby Magnum

.243"	6mm
	Spitzer BTSP
Weight (grains)	100
Ballistic Coefficient	0.446
Sectional Density	0.242
COAL Tested	3.060"
Speer Part No.	1220

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Winchester 760	Weatherby	CCI 250	45.0	2922	49.0	3209
Hodgdon H414	Weatherby	CCI 250	46.0	2897	50.0	3167
IMR 4831	Weatherby	CCI 250	45.5	2915	49.5 C	3154
IMR 4350	Weatherby	CCI 250	43.5	2768	47.5	3007
IMR 4064	Weatherby	CCI 250	38.0	2714	42.0	2977
Hodgdon H380	Weatherby	CCI 250	41.0	2601	45.0	2901

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load