



243 Winchester Super Short Magnum

.243"	6mm
	Spitzer BTSP
Weight (grains)	100
Ballistic Coefficient	0.446
Sectional Density	0.242
COAL Tested	2.360"
Speer Part No.	1220

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Ramshot Magnum	Winchester	Federal 215	50.5	2993	52.5 C	3116
Alliant Reloder 22	Winchester	Federal 210	41.5	2920	43.5	3004
Vihtavuori N560	Winchester	Federal 210	40.0	2860	42.0	2948
Alliant Reloder 19	Winchester	Federal 210	38.5	2829	40.5	2915
Accurate 4350	Winchester	Federal 210	38.5	2785	40.5	2904
IMR 4350	Winchester	Federal 210	36.5	2792	38.5	2894
Hodgdon H4350	Winchester	Federal 210	35.5	2780	37.5	2881
Hodgdon H414	Winchester	Federal 215	36.0	2745	38.0	2856
Winchester 760	Winchester	Federal 215	35.5	2733	37.5	2835

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load