



6mm Remington

.243"	6mm
Weight (grains)	Spitzer BTSP
Ballistic Coefficient	85
Sectional Density	0.380
COAL Tested	0.206
Speer Part No.	2.775"
	1213

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Alliant Power Pro 4000-MR	Federal	Federal 210	46.4	3284	48.5 C	3411
Alliant Reloder 16	Federal	Federal 210	41.9	3221	43.9	3354
Vihtavouri N550	Federal	Federal 210	42.0	3271	43.5	3372
Hodgdon H4350	Federal	Federal 210	44.0	3215	46.4	3371
Alliant Reloder 23	Federal	Federal 210	45.0	3175	48.0 C	3368
Alliant Power Pro 2000-MR	Federal	Federal 210	40.5	3219	42.1	3334
Alliant Reloder 22	Remington	CCI 200	48.0	3048	52.0 C	3285
Alliant Reloder 19	Remington	CCI 200	46.5	3007	50.5 C	3269
Accurate 4350	Remington	CCI 200	45.0	2878	49.0	3264
Hodgdon H4831	Remington	CCI 250	47.0	2968	51.0 C	3226
Winchester 760	Remington	CCI 250	41.0	2859	46.0	3152
IMR 4350	Remington	CCI 200	41.0	2881	46.0	3138
Accurate 2700	Remington	CCI 250	40.5	2846	44.5	3128
IMR 4831	Remington	CCI 200	43.0	2838	47.0	3085
Accurate 2520	Remington	CCI 250	36.0	2786	40.0	3061
Hodgdon H380	Remington	CCI 250	39.0	2777	43.0	3052
IMR 4895	Remington	CCI 200	35.0	2742	39.0	3000
IMR 4064	Remington	CCI 200	36.0	2704	40.0	2965
Vihtavuori N140	Remington	CCI 200	35.5	2723	39.5	2960
Hodgdon H414	Remington	CCI 250	40.0	2685	44.0	2921

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load