



## 25-06 Remington

<b>.257"</b>	<b>25</b>
<b>Weight (grains)</b>	<b>Spitzer BTSP</b>
<b>Ballistic Coefficient</b>	120
<b>Sectional Density</b>	0.480
<b>COAL Tested</b>	0.260
<b>Speer Part No.</b>	3.200"
	1410

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Alliant Reloder 25	Winchester	CCI 200	56.0	2971	<b>58.0 C</b>	3071
Alliant Reloder 26	Federal	Federal 210	49.0	2770	<b>53.2</b>	3024
Alliant Reloder 23	Federal	Federal 210	46.5	2718	<b>51.0</b>	3010
Hodgdon H870	Winchester	CCI 250	60.0	2791	<b>64.0 C</b>	3006
IMR 4350	Winchester	CCI 200	44.5	2773	<b>48.5</b>	2990
IMR 4831	Winchester	CCI 200	46.0	2769	<b>50.0</b>	2980
Alliant Reloder 17	Federal	Federal 210	43.0	2708	<b>47.2</b>	2972
Hodgdon H4831SC	Winchester	CCI 200	48.0	2769	<b>52.0</b>	2958
Alliant Reloder 22	Winchester	CCI 200	48.0	2699	<b>52.0</b>	2931
Alliant Power Pro 4000-MR	Federal	Federal 210	44.5	2682	<b>48.7</b>	2929
Hodgdon H1000	Winchester	CCI 200	51.0	2644	<b>55.0</b>	2922
IMR 7828	Winchester	CCI 200	51.0	2644	<b>55.0</b>	2885
Accurate 4350	Winchester	CCI 200	45.0	2655	<b>49.0</b>	2843
Accurate 3100	Winchester	CCI 200	47.0	2567	<b>51.0</b>	2818
Hodgdon H4350	Winchester	CCI 200	44.0	2577	<b>48.0</b>	2792
IMR SR 4759 (reduced load)	Winchester	CCI 200	17.0	1501	<b>21.0</b>	1861

**WARNING:** Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

*Maximum loads should be used with CAUTION • C = Compressed Load*