



257 Weatherby Magnum

.257"	25 Spitzer SP Hot- Cor®	25 HP	25 Spitzer BTSP
Weight (grains)	100	100	100
Ballistic Coefficient	0.334	0.263	0.393
Sectional Density	0.216	0.216	0.216
COAL Tested	3.150"	3.140"	3.150"
Speer Part No.	1405	1407	1408

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Alliant Reloder 25	Federal	CCI 250	69.0	3395	73.0	3545
Ramshot Magnum	Federal	CCI 250	70.0	3339	74.0	3494
Alliant Reloder 33	Weatherby	CCI 250	75.0	3092	82.9 C	3483
Alliant Reloder 26	Weatherby	CCI 250	63.6	3116	70.7	3483
Alliant Reloder 22	Federal	CCI 250	64.0	3225	68.0	3450
Alliant Reloder 23	Weatherby	CCI 250	62.5	3104	69.6	3450
IMR 7828	Federal	CCI 250	67.0	3306	69.0	3447
Alliant Power Pro 4000-MR	Weatherby	CCI 250	59.4	3111	66.0	3428
Vihavuori N560	Federal	CCI 250	65.0	3290	67.0	3413
Hodgdon Retumbo	Federal	CCI 250	71.0	3283	73.0	3411
Hodgdon H1000	Federal	CCI 250	69.0	3302	71.0	3405
Alliant Reloder 19	Federal	CCI 250	61.0	3188	65.0	3405
IMR 7977	Weatherby	CCI 250	66.7	3065	73.9	3399
Accurate MagPro	Federal	CCI 250	65.0	3197	67.0	3292

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load