



257 Weatherby Magnum

.257"	25
Weight (grains)	Spitzer BTSP
Ballistic Coefficient	120
Sectional Density	0.480
COAL Tested	0.260
Speer Part No.	3.170"
	1410

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Alliant Reloder 33	Weatherby	CCI 250	69.7	2953	77.4	3242
Alliant Reloder 25	Federal	CCI 250	63.0	3024	67.0	3236
Ramshot Magnum	Federal	CCI 250	66.0	3046	70.0	3211
Alliant Reloder 26	Weatherby	CCI 250	59.3	2901	65.9	3197
Vihtavuori N560	Federal	CCI 250	60.0	2963	64.0	3181
Alliant Reloder 23	Weatherby	CCI 250	60.8	3031	64.2	3164
Hodgdon Retumbo	Federal	CCI 250	65.0	2948	69.0	3159
Alliant Power Pro 4000-MR	Weatherby	CCI 250	56.9	2920	61.9	3148
IMR 7977	Weatherby	CCI 250	62.1	2875	68.9	3146
Alliant Reloder 22	Federal	CCI 250	59.0	2904	63.0	3120
Hodgdon H1000	Federal	CCI 250	64.5	3006	66.5	3108
IMR 7828	Federal	CCI 250	62.0	2988	64.0	3106
Hodgdon H4831SC	Federal	CCI 250	61.0	3000	63.0	3103
Accurate MagPro	Federal	CCI 250	62.0	2927	64.0	3027

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load