



6.8mm Remington SPC

.277"	270
	HP
Weight (grains)	100
Ballistic Coefficient	0.201
Sectional Density	0.186
COAL Tested	2.250"
Speer Part No.	1447

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Alliant Power Pro Varmint	Federal	GM205MAR	30.6	2712	33.9 C	2982
Alliant Power Pro 1200-R	Federal	GM205MAR	27.1	2711	30.1	2947
Ramshot X-Terminator	Remington	CCI 200	31.0	2653	33.0	2815
Alliant Reloder 10X	Remington	CCI 200	26.5	2607	28.5 C	2791
Hodgdon H322	Remington	CCI 200	27.5	2592	29.5 C	2778
Hodgdon H335	Remington	CCI 200	31.0	2590	33.0 C	2739
Hodgdon BL-C(2)	Remington	CCI 200	32.0	2614	34.0 C	2727
IMR 4198	Remington	CCI 200	23.0	2566	25.0	2718
Alliant Reloder 7	Remington	CCI 200	24.0	2524	26.0	2715
Accurate 1680	Remington	CCI 200	24.0	2517	26.0	2702
Vihtavuori N120	Remington	CCI 200	22.5	2504	24.5	2680
Accurate 2015	Remington	CCI 200	27.0	2504	29.0 C	2677
Accurate 5744	Remington	CCI 200	21.0	2408	23.0	2582

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load