



6.8mm Remington SPC

.277"	270
	TNT® HP
Weight (grains)	90
Ballistic Coefficient	0.303
Sectional Density	0.168
COAL Tested	2.250"
Speer Part No.	1446

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Alliant Power Pro® 1200-R	Federal®	CCI 400	30.3	3045	31.6	3170
Alliant Power Pro Varmint	Federal	CCI 400	33.9 C	3008	35.6 C	3170
Accurate 2230	Remington	CCI 200	31.5	2942	33.5 C	3067
Hodgdon H322	Remington	CCI 200	29.0	2824	31.0 C	2995
Hodgdon H335	Remington	CCI 200	33.0	2852	35.0 C	2995
Alliant Reloder® 10X	Remington	CCI 200	27.5	2822	29.5	2991
Alliant Reloder 7	Remington	CCI 200	25.5	2782	27.5	2983
Ramshot X-Terminator	Remington	CCI 200	31.5	2833	33.5 C	2968
Accurate 2015	Remington	CCI 200	28.5	2746	30.5 C	2924
IMR 4198	Remington	CCI 200	23.5	2733	25.5	2915
Accurate 1680	Remington	CCI 200	25.0	2740	27.0	2906
Vihtavuori N120	Remington	CCI 200	23.5	2717	25.5	2905
Accurate 5744	Remington	CCI 200	21.5	2597	23.5	2787
IMR 4227	Remington	CCI 200	20.0	2579	22.0	2749

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load