



6.8mm Remington SPC

.277"	27
	GD
Weight (grains)	115
Ballistic Coefficient	0.401
Sectional Density	0.214
COAL Tested	2.260"
Speer Part No.	277115GDB

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Hodgdon CFE 223	Federal	GM205MAR	30.3	2534	33.6 C	2771
Accurate 2230	Federal	GM205MAR	27.0	2493	30.0	2705
Alliant Power Pro Varmint	Federal	GM205MAR	28.0	2482	31.1 C	2699
Accurate 2200	Federal	GM205MAR	24.7	2441	27.4	2688
Hodgdon H335	Federal	GM205MAR	26.7	2429	29.7	2671
Alliant Power Pro 1200-R	Federal	GM205MAR	24.9	2444	27.6	2666
Ramshot X-Terminator	Federal	GM205MAR	26.4	2427	29.2	2637
Hodgdon BENCHMARK	Federal	GM205MAR	25.8	2380	28.7	2628
Alliant Reloder 10X	Federal	GM205MAR	24.0	2362	26.7	2626
Alliant Reloder 7	Federal	GM205MAR	22.9	2357	25.3	2573
Vihtavuori N130	Federal	GM205MAR	22.9	2353	25.3	2554

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load