



30-06 Springfiled

.308"	30
Weight (grains)	Varminter HP
Ballistic Coefficient	110
Sectional Density	0.128
COAL Tested	0.166
Speer Part No.	2.870"
	1835

NOTE: This bullet not intended for velocities in excess of 2900 fps.

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Winchester 760	Winchester	CCI 250	52.0	2682	56.0	2904
Winchester 748	Winchester	CCI 250	44.5	2631	48.5	2888
IMR 4350	Winchester	CCI 200	54.0	2651	58.0	2873
IMR 3031	Winchester	CCI 200	42.5	2601	46.5	2871
IMR 4895	Winchester	CCI 200	44.0	2588	48.0	2847
Alliant Reloder 7	Winchester	CCI 200	38.0	2541	42.0	2836
Hodgdon H322	Winchester	CCI 200	41.0	2530	45.0	2769
Hodgdon BL-C(2)	Winchester	CCI 250	48.0	2537	52.0	2766
IMR 4227 (reduced load)	Winchester	CCI 200	29.0	2316	31.0	2500

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load