



## 30-30-Winchester

<b>.308"</b>	<b>30 Varminter HP</b>
<b>Weight (grains)</b>	110
<b>Ballistic Coefficient</b>	0.128
<b>Sectional Density</b>	0.166
<b>COAL Tested</b>	2.415"
<b>Speer Part No.</b>	1835

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Alliant Reloder 7	Winchester	CCI 200	30.0	2341	<b>34.0</b>	2775
Hodgdon H322	Winchester	CCI 200	31.0	2264	<b>35.0</b>	2652
Accurate 2015	Winchester	CCI 200	30.0	2290	<b>34.0</b>	2649
Winchester 748	Winchester	CCI 250	36.0	2292	<b>40.0 C</b>	2621
IMR 4064	Winchester	CCI 200	33.0	2117	<b>37.0 C</b>	2509
Hodgdon BL-C(2)	Winchester	CCI 250	33.0	2116	<b>37.0</b>	2477
IMR 4895	Winchester	CCI 200	31.0	2127	<b>35.0</b>	2461
Vihtavuori N133	Winchester	CCI 200	27.0	1950	<b>31.0</b>	2405
Hodgdon H4895	Winchester	CCI 200	30.0	1972	<b>34.0 C</b>	2339
IMR 4350	Winchester	CCI 200	36.0	1995	<b>40.0 C</b>	2337
Accurate 2230	Winchester	CCI 200	27.0	2018	<b>31.0</b>	2335
Accurate 2460	Winchester	CCI 250	28.0	2007	<b>32.0</b>	2295

**WARNING:** Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

*Maximum loads should be used with CAUTION • C = Compressed Load*