



30-30 Winchester

.308"	30 SPFN Hot-Cor®
Weight (grains)	150
Ballistic Coefficient	0.255
Sectional Density	0.226
COAL Tested	2.550"
Speer Part No.	2011

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Alliant Power Pro 2000-MR	Federal	Federal 210	37.2	2321	41.0 C	2539
Hodgdon LEVERevolution	Federal	Federal 210	35.2	2332	38.2 C	2516
Hodgdon CFE 223	Federal	Federal 210	36.3	2318	39.9 C	2511
Alliant AR-Comp	Federal	Federal 210	31.2	2266	33.8	2425
Alliant Power Pro Varmint	Federal	Federal 210	30.2	2168	33.4	2355
Winchester 748	Winchester	CCI 250	33.0	1941	37.0 C	2273
Hodgdon H322	Winchester	CCI 200	27.0	1899	31.0	2253
Accurate 2520	Winchester	CCI 250	28.0	1875	32.0	2224
Alliant Reloder 7	Winchester	CCI 200	25.0	1895	29.0	2220
Alliant Reloder 15	Winchester	CCI 200	30.0	1833	34.0 C	2201
Vihtavuori N140	Winchester	CCI 200	30.0	1866	34.0	2186
Hodgdon Varget	Winchester	CCI 200	29.0	1835	33.0	2168
Alliant Reloder 10X	Winchester	CCI 200	24.0	1850	28.0	2144
Hodgdon H335	Winchester	CCI 250	28.0	1736	32.0	2138
Hodgdon H414	Winchester	CCI 250	34.0	1729	38.0 C	2103
IMR 4320	Winchester	CCI 200	29.0	1702	33.0	2070
Hodgdon H4895	Winchester	CCI 200	27.0	1675	31.0	2064
IMR 4895	Winchester	CCI 200	27.0	1701	31.0	2039
IMR 4350	Winchester	CCI 200	32.0	1692	36.0 C	2033

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load