



## 300 Holland & Holland Magnum

<b>.308"</b>	<b>30</b>
	<b>HP</b>
<b>Weight (grains)</b>	130
<b>Ballistic Coefficient</b>	0.244
<b>Sectional Density</b>	0.196
<b>COAL Tested</b>	3.440"
<b>Speer Part No.</b>	2005

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
<b>Alliant Reloder 16</b>	Federal	Federal 215	67.2	3100	<b>74.4</b>	3433
<b>Alliant Power Pro 4000-MR</b>	Federal	Federal 215	68.4	3090	<b>75.5</b>	3417
<b>IMR 4831</b>	Winchester	CCI 200	70.0	3145	<b>74.0 C</b>	3330
<b>IMR 4350</b>	Winchester	CCI 200	68.0	3080	<b>72.0 C</b>	3316
<b>IMR 3031</b>	Winchester	CCI 200	55.0	3046	<b>59.0</b>	3255
<b>Accurate 4350</b>	Winchester	CCI 250	70.0	3014	<b>74.0</b>	3245
<b>Alliant Reloder 19</b>	Winchester	CCI 250	71.0	3050	<b>75.0</b>	3244
<b>Accurate 3100</b>	Winchester	CCI 250	74.0	3055	<b>78.0 C</b>	3236
<b>IMR 4064</b>	Winchester	CCI 200	58.0	2967	<b>62.0</b>	3205
<b>Vihtavuori N160</b>	Winchester	CCI 250	66.0	2941	<b>70.0</b>	3174
<b>Winchester 760</b>	Winchester	CCI 250	65.0	2910	<b>69.0</b>	3143
<b>IMR 4895</b>	Winchester	CCI 200	55.0	2939	<b>59.0</b>	3116
<b>Hodgdon H380</b>	Winchester	CCI 250	58.0	2730	<b>62.0</b>	2976
<b>IMR SR 4759 (reduced load)</b>	Winchester	CCI 200	22.0	1735	<b>24.0</b>	1894

**WARNING:** Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

*Maximum loads should be used with CAUTION • C = Compressed Load*