



300 Weatherby Magnum

.308"	30 HP
Weight (grains)	130
Ballistic Coefficient	0.244
Sectional Density	0.196
COAL Tested	3.530"
Speer Part No.	2005

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Alliant Reloder 26	Federal	Federal 215	82.4	3236	91.6	3674
Alliant Reloder 23	Federal	Federal 215	80.0	3246	88.5 C	3600
Alliant Power Pro 4000-MR	Federal	Federal 215	75.6	3229	83.6	3586
Alliant Reloder 22	Federal	Federal 215	78.3	3169	86.3	3576
Vihtavuori N560	Federal	Federal 215	79.9	3099	88.7	3534
IMR 7977	Federal	Federal 215	83.7	3152	93.0 C	3513
Alliant Reloder 19	Remington	CCI 250	82.0	3190	86.0	3432
Hodgdon H4350	Remington	CCI 250	77.5	3148	81.5	3404
Accurate 3100	Remington	CCI 250	81.0	3169	85.0 C	3368
IMR 7828	Remington	CCI 250	84.0	3168	88.0 C	3361
IMR 4831	Remington	CCI 250	79.0	3089	83.0	3344
Hodgdon H4831SC	Remington	CCI 250	82.0	3151	86.0 C	3327
IMR 4350	Remington	CCI 250	77.0	3061	81.0	3291
Accurate 4350	Remington	CCI 250	75.0	3050	79.0	3289
Hodgdon H4895	Remington	CCI 250	66.0	3080	70.0	3248

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load