



300 Weatherby Magnum

.308"	30 Spitzer SP Hot- Cor®
Weight (grains)	200
Ballistic Coefficient	0.478
Sectional Density	0.301
COAL Tested	3.560"
Speer Part No.	2211

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Hodgdon H870	Remington	CCI 250	90.0	2847	94.0 C	2997
Alliant Reloder 25	Remington	CCI 250	81.0	2801	85.0 C	2977
Alliant Reloder 26	Federal	Federal 215	72.4	2609	80.2	2950
Hodgdon Retumbo	Federal	Federal 215	77.5	2655	85.3 C	2915
Alliant Reloder 23	Federal	Federal 215	70.4	2657	77.4	2895
IMR 7977	Federal	Federal 215	74.9	2529	83.1 C	2883
Hodgdon H1000	Remington	CCI 250	78.0	2712	82.0	2867
Alliant Reloder 22	Remington	CCI 250	74.5	2684	78.5	2841
Alliant Reloder 19	Remington	CCI 250	73.0	2701	77.0	2839
Accurate 8700	Remington	CCI 250	92.0	2785	94.0 C	2819
IMR 7828	Remington	CCI 250	73.0	2591	77.0	2803
Hodgdon H4831SC	Remington	CCI 250	72.5	2624	76.5	2801
Accurate 3100	Remington	CCI 250	71.0	2602	75.0	2786
IMR 4831	Remington	CCI 250	69.0	2598	73.0	2743
Accurate 4350	Remington	CCI 250	66.0	2445	70.0	2689
IMR 4350	Remington	CCI 250	65.0	2440	69.0	2648
Hodgdon H414	Remington	CCI 250	64.0	2484	68.0	2629
Hodgdon H4350	Remington	CCI 250	65.0	2454	69.0	2618

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load