



## 300 Winchester Magnum

<b>.308"</b>	<b>30</b>
	<b>Spitzer SP Hot-</b>
	<b>Cor®</b>
<b>Weight (grains)</b>	200
<b>Ballistic Coefficient</b>	0.478
<b>Sectional Density</b>	0.301
<b>COAL Tested</b>	3.340"
<b>Speer Part No.</b>	2211

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Alliant Reloder 26	Federal	Federal 215	67.2	2619	<b>74.0 C</b>	2884
Alliant Reloder 25	Winchester	CCI 250	71.0	2735	<b>75.0 C</b>	2857
IMR 7828	Winchester	CCI 250	71.0	2656	<b>75.0 C</b>	2856
Alliant Reloder 23	Federal	Federal 215	66.8	2599	<b>74.0 C</b>	2855
Alliant Reloder 22	Winchester	CCI 250	69.0	2652	<b>73.0 C</b>	2852
IMR 4350	Winchester	CCI 250	65.0	2672	<b>69.0</b>	2843
Alliant Reloder 17	Federal	Federal 215	61.3	2606	<b>68.1</b>	2826
Alliant Power Pro 4000-MR	Federal	Federal 215	63.3	2548	<b>70.1</b>	2817
Hodgdon H1000	Winchester	CCI 250	73.0	2629	<b>77.0 C</b>	2797
Hodgdon H4350	Winchester	CCI 250	65.0	2637	<b>69.0</b>	2776
Hodgdon H4831SC	Winchester	CCI 250	67.0	2653	<b>71.0</b>	2770
Vihtavuori N165	Winchester	CCI 250	68.0	2601	<b>72.0</b>	2767
Alliant Reloder 19	Winchester	CCI 250	67.0	2582	<b>71.0</b>	2761
Hodgdon H870	Winchester	CCI 250	81.0	2579	<b>85.0 C</b>	2758
Winchester 760	Winchester	CCI 250	60.0	2605	<b>64.0</b>	2742
Hodgdon H414	Winchester	CCI 250	60.0	2597	<b>64.0</b>	2741
Accurate 4350	Winchester	CCI 250	63.0	2544	<b>67.0</b>	2735
Accurate 3100	Winchester	CCI 250	69.0	2496	<b>73.0 C</b>	2641
IMR 4198 (reduced load)	Winchester	CCI 250	31.0	1812	<b>35.0</b>	2036

**WARNING:** Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

*Maximum loads should be used with CAUTION • C = Compressed Load*