



307 Winchester

.308"	30
Weight (grains)	100
Ballistic Coefficient	0.144
Sectional Density	0.151
COAL Tested	2.390"
Speer Part No.	1805

**30
Plinker® SPRN**

NOTE: COAL less than minimum. We recommend single loading into the chamber.

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Alliant Reloder 7	Winchester	CCI 200	33.0	2524	37.0	2838
IMR 4320	Winchester	CCI 200	38.0	2448	42.0	2691
IMR 4198	Winchester	CCI 200	28.0	2424	32.0	2659
IMR 3031	Winchester	CCI 200	36.0	2178	40.0	2584
Alliant 2400	Winchester	CCI 200	20.0	2211	24.0	2564
IMR 4895	Winchester	CCI 200	36.0	2286	40.0	2524
Winchester 748	Winchester	CCI 250	38.0	2297	42.0	2489
Hodgdon H322	Winchester	CCI 200	31.0	2185	35.0	2466

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load