



## 308 Winchester

<b>.308"</b>	<b>30</b>
	<b>GD</b>
<b>Weight (grains)</b>	168
<b>Ballistic Coefficient</b>	0.572
<b>Sectional Density</b>	0.253
<b>COAL Tested</b>	2.800"
<b>Speer Part No.</b>	308168GDB

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Alliant Power Pro 2000-MR	Federal	Federal 210	45.3	2564	<b>50.2 C</b>	2821
Hodgdon CFE 223	Federal	Federal 210	43.2	2507	<b>47.7</b>	2729
Accurate 2520	Federal	Federal 210	40.9	2500	<b>45.3</b>	2725
Alliant Power Pro Varmint	Federal	Federal 210	40.0	2466	<b>44.4</b>	2709
Alliant Reloder 15	Federal	Federal 210	40.7	2455	<b>45.2</b>	2704
Winchester 748	Federal	Federal 210	41.5	2436	<b>46.1</b>	2696
Accurate 4064	Federal	Federal 210	41.0	2409	<b>45.5 C</b>	2665
Hodgdon Varget	Federal	Federal 210	39.6	2402	<b>43.9</b>	2665
IMR 4895	Federal	Federal 210	39.0	2380	<b>43.3</b>	2661
IMR 4064	Federal	Federal 210	39.5	2396	<b>43.6 C</b>	2660
Vihtavuori N540	Federal	Federal 210	41.0	2379	<b>45.3</b>	2660
Alliant AR-Comp	Federal	Federal 210	38.0	2419	<b>42.2</b>	2640

**WARNING:** Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

*Maximum loads should be used with CAUTION • C = Compressed Load*