



338-06 A-Square

.338"	338
	Spitzer SP Hot-Cor®
Weight (grains)	200
Ballistic Coefficient	0.426
Sectional Density	0.250
COAL Tested	3.340"
Speer Part No.	2405

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Hodgdon H4350	Reformed Rem 35 Whelen	CCI 200	59.0	2617	63.0 C	2791
IMR 4064	Reformed Rem 35 Whelen	CCI 200	52.0	2582	56.0	2784
IMR 4320	Reformed Rem 35 Whelen	CCI 200	52.5	2578	56.5	2777
Alliant Reloder 15	Reformed Rem 35 Whelen	CCI 200	51.0	2566	55.0	2769
Vihtavuori N150	Reformed Rem 35 Whelen	CCI 200	52.5	2572	56.5	2769
Hodgdon H380	Reformed Rem 35 Whelen	CCI 200	58.0	2587	62.0 C	2767
Winchester 760	Reformed Rem 35 Whelen	CCI 200	58.5	2577	62.5 C	2757
IMR 4350	Reformed Rem 35 Whelen	CCI 200	58.0	2574	62.0 C	2753
Accurate 4350	Reformed Rem 35 Whelen	CCI 200	60.5	2578	64.5 C	2750
Hodgdon H414	Reformed Rem 35 Whelen	CCI 200	58.5	2564	62.5	2741

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load