



338 Winchester Magnum

.338"	338
	Spitzer SP Hot-
	Cor®
Weight (grains)	200
Ballistic Coefficient	0.426
Sectional Density	0.250
COAL Tested	3.300"
Speer Part No.	2405

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Alliant Power Pro 4000-MR	Federal	Federal 215	70.9	2808	78.8 C	3059
Alliant Reloder 16	Federal	Federal 215	67.1	2799	74.3 C	3041
Alliant Reloder 17	Federal	Federal 215	66.7	2751	74.0	3009
IMR 4451	Federal	Federal 215	67.7	2696	75.7 C	2966
IMR 4350	Winchester	CCI 250	69.5	2791	73.5	2959
IMR 4831	Winchester	CCI 250	70.5	2782	74.5	2956
Hodgdon H4350	Winchester	CCI 250	71.0	2697	75.0 C	2932
Hodgdon H414	Winchester	CCI 250	66.0	2793	70.0	2905
Hodgdon H4831SC	Winchester	CCI 250	74.0	2781	78.0 C	2887
IMR 7828	Winchester	CCI 250	77.0	2682	81.0 C	2882
Vihtavuori N150	Winchester	CCI 250	61.0	2598	65.0	2824
Accurate 3100	Winchester	CCI 250	73.0	2654	77.0 C	2823
Winchester 760	Winchester	CCI 250	66.0	2604	70.0	2816
Alliant Reloder 19	Winchester	CCI 250	72.0	2596	76.0 C	2806
Accurate 2700	Winchester	CCI 250	65.0	2550	69.0	2757
IMR 3031	Winchester	CCI 250	55.0	2469	59.0	2627
IMR 4064	Winchester	CCI 250	57.0	2440	61.0	2610

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load