



35 Whelen

.358"	35 SPFN Hot-Cor®
Weight (grains)	180
Ballistic Coefficient	0.236
Sectional Density	0.201
COAL Tested	3.030"
Speer Part No.	2435

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Alliant Power Pro Varmint	Federal	Federal 210	63.0	2911	70.0 C	3172
IMR 8208 XBR	Federal	Federal 210	59.6	2918	63.8 C	3080
Alliant Power Pro 1200-R	Federal	Federal 210	51.2	2793	56.1	2984
Alliant AR-Comp	Federal	Federal 210	57.6	2713	63.0 C	2950
Hodgdon H335	Remington	CCI 250	61.0	2841	65.0 C	2931
Hodgdon CFE 223	Federal	Federal 210	65.7	2775	69.0 C	2904
Accurate 2460	Remington	CCI 250	56.0	2291	60.0 C	2899
Accurate 2230	Remington	CCI 200	54.0	2703	58.0 C	2891
Hodgdon BL-C(2)	Remington	CCI 250	60.0	2719	64.0	2863
Accurate 2015	Remington	CCI 200	50.0	2591	54.0	2834
Hodgdon H322	Remington	CCI 200	54.0	2676	58.0 C	2834
Hodgdon H4895	Remington	CCI 200	54.0	2623	58.0 C	2818
Vihtavuori N140	Remington	CCI 200	58.0	2667	62.0 C	2807
IMR 4895	Remington	CCI 200	53.0	2538	57.0 C	2797
IMR 3031	Remington	CCI 200	53.0	2497	57.0 C	2775
IMR 4064	Remington	CCI 200	56.0	2536	60.0 C	2765
Alliant Reloder 15	Remington	CCI 200	56.0	2511	60.0 C	2710

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load