



416 Remington Magnum

.416"

416
Mag-Tip SP Hot-
Cor®

Weight (grains)	350
Ballistic Coefficient	0.332
Sectional Density	0.289
COAL Tested	3.580"
Speer Part No.	2477

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Alliant Power Pro 2000-MR	Federal	Federal 215	87.8	2574	97.3 C	2811
Alliant Reloder 17	Federal	Federal 215	84.9	2478	93.9 C	2733
Alliant Power Pro Varmint	Federal	Federal 215	77.0	2484	85.4	2683
Alliant AR-Comp	Federal	Federal 215	75.6	2426	83.9 C	2652
Vihtavuori N540	Remington	CCI 250	78.0	2553	82.0	2636
Alliant Reloder 15	Remington	CCI 250	81.0	2541	85.0	2629
Hodgdon BL-C(2)	Remington	CCI 250	83.0	2496	87.0	2586
IMR 4064	Remington	CCI 250	77.0	2468	81.0	2565
IMR 4451	Federal	Federal 215	81.0	2343	90.0 C	2563
Vihtavuori N140	Remington	CCI 250	76.0	2410	80.0	2512
Accurate 2520	Remington	CCI 250	71.0	2364	75.0	2465
IMR 3031	Remington	CCI 250	69.0	2375	73.0	2456
IMR 4895	Remington	CCI 250	70.0	2326	74.0	2420

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load