



## 45-70 Government (Trapdoor Actions)

<b>.458"</b>	<b>45</b>
	<b>SPFN Hot-Cor®</b>
<b>Weight (grains)</b>	350
<b>Ballistic Coefficient</b>	0.218
<b>Sectional Density</b>	0.238
<b>COAL Tested</b>	2.715"
<b>Speer Part No.</b>	2478

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
<b>Accurate 2015</b>	Winchester	CCI 200	46.0	1520	<b>50.0</b>	1713
<b>Hodgdon BENCHMARK</b>	Winchester	CCI 200	47.0	1551	<b>51.0</b>	1699
<b>Vihtavuori N133</b>	Winchester	CCI 200	44.0	1479	<b>48.0</b>	1699
<b>IMR 8208</b>	Winchester	CCI 200	47.0	1555	<b>50.9</b>	1697
<b>IMR 4064</b>	Winchester	CCI 200	51.0	1516	<b>55.0</b>	1633
<b>Hodgdon H4895</b>	Winchester	CCI 200	48.0	1464	<b>52.0</b>	1626
<b>IMR 4198</b>	Winchester	CCI 200	32.0	1427	<b>36.0</b>	1609
<b>IMR 3031</b>	Winchester	CCI 200	48.0	1397	<b>52.0</b>	1587
<b>IMR 4166</b>	Winchester	CCI 200	41.0	1402	<b>45.0</b>	1528
<b>Alliant Reloder 10X</b>	Winchester	CCI 200	32.0	1355	<b>36.0</b>	1485
<b>IMR SR 4759</b>	Winchester	CCI 200	26.0	1381	<b>30.0</b>	1468
<b>Alliant Reloder 7</b>	Winchester	CCI 200	31.0	1303	<b>35.0</b>	1463

**WARNING:** Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

*Maximum loads should be used with CAUTION • C = Compressed Load*