



458 Winchester Magnum

.458"	45
Weight (grains)	350
Ballistic Coefficient	0.218
Sectional Density	0.238
COAL Tested	3.105"
Speer Part No.	2478

45
SPFN Hot-Cor®

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Accurate 2230	Winchester	CCI 250	82.0	2499	86.0 C	2593
Accurate 2015	Winchester	CCI 250	73.0	2419	77.0 C	2560
Hodgdon H322	Winchester	CCI 250	78.0	2399	82.0 C	2524
IMR 4198	Winchester	CCI 250	67.0	2399	71.0 C	2505
Vihtavuori N133	Winchester	CCI 250	72.0	2233	76.0 C	2471
IMR 4895	Winchester	CCI 250	76.0	2331	80.0 C	2467
IMR 4166	Federal	CCI 250	78.5	2376	80.9 C	2445
Hodgdon H335	Winchester	CCI 250	81.0	2227	85.0 C	2418
Accurate 2460	Winchester	CCI 250	75.0	2261	79.0 C	2371
Hodgdon BL-C(2)	Winchester	CCI 250	80.0	2204	84.0 C	2343
Alliant Reloder 7	Winchester	CCI 250	69.0	2186	73.0 C	2335
IMR 3031	Winchester	CCI 250	71.0	2165	75.0 C	2314

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load