



6.5 Creedmoor

| | |
|------------------------------|----------------|
| .264" | 6.5mm |
| Weight (grains) | TNT® HP |
| Ballistic Coefficient | 90 |
| Sectional Density | 0.281 |
| COAL Tested | 0.184 |
| Speer Part No. | 2.700" |
| | 1445 |

| Propellant | Case | Primer | START CHARGE | | MAXIMUM CHARGE | |
|---------------------------|---------|---------|-----------------|----------------------------|-----------------|----------------------------|
| | | | Weight (grains) | Muzzle Velocity (feet/sec) | Weight (grains) | Muzzle Velocity (feet/sec) |
| Alliant Reloder 17 | Hornady | CCI 200 | 45.2 | 3120 | 50.0 C | 3499 |
| Alliant Power Pro 2000-MR | Hornady | CCI 200 | 44.6 | 3112 | 49.5 | 3491 |
| Accurate 2700 | Hornady | CCI 200 | 46.2 | 3184 | 49.8 | 3474 |
| Hodgdon H414 | Hornady | CCI 200 | 45.7 | 3125 | 49.7 | 3437 |
| Alliant Power Pro Varmint | Hornady | CCI 200 | 40.9 | 3097 | 45.3 | 3433 |
| Alliant Reloder 15 | Hornady | CCI 200 | 42.9 | 3195 | 46.1 | 3430 |
| IMR 4064 | Hornady | CCI 200 | 40.2 | 3111 | 44.1 | 3420 |
| Hodgdon Varget | Hornady | CCI 200 | 41.1 | 3141 | 44.7 | 3415 |
| Hodgdon H380 | Hornady | CCI 200 | 45.1 | 3109 | 49.0 C | 3382 |
| Alliant AR-Comp | Hornady | CCI 200 | 38.3 | 3010 | 42.6 | 3372 |
| Vihtavuori N140 | Hornady | CCI 200 | 39.8 | 3008 | 44.1 | 3343 |

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load