



speer®
bullets

6.5 Grendel

.264"	6.5mm
	Spitzer SP Hot-
	Cor®
Weight (grains)	140
Ballistic Coefficient	0.498
Sectional Density	0.287
COAL Tested	2.140"
Speer Part No.	1441

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Winchester 748	Federal	Federal 205	25.4 C	2064	28.6 C	2338
Alliant Power Pro Varmint	Federal	Federal 205	25.1 C	2111	27.7 C	2323
Hodgdon CFE 223	Federal	Federal 205	25.4	2090	28.2 C	2315
Ramshot TAC	Federal	Federal 205	24.0	2070	26.5	2250
IMR 8208 XBR	Federal	Federal 205	22.9	2018	25.4 C	2230
Alliant AR-Comp	Federal	Federal 205	22.2	2025	24.4 C	2186
Vituvori N135	Federal	Federal 205	21.6 C	1972	23.9 C	2128
Accurate 4064	Federal	Federal 205	23.6	1943	24.5 C	2039

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load