



## 284 Winchester

.284"	7mm Spitzer SP Hot- Cor®	7mm Spitzer BTSP
Weight (grains)	130	130
Ballistic Coefficient	0.368	0.424
Sectional Density	0.230	0.230
COAL Tested	2.800"	2.800"
Speer Part No.	1623	1624

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
IMR 4350	Winchester	CCI 200	54.0	2933	<b>58.0</b>	3148
IMR 4831	Winchester	CCI 200	55.0	2884	<b>59.0</b>	3085
Winchester 760	Winchester	CCI 250	52.0	2815	<b>56.0</b>	3047
Winchester 748	Winchester	CCI 250	46.0	2693	<b>50.0</b>	2935
IMR 4064	Winchester	CCI 200	45.0	2636	<b>49.0</b>	2879
IMR SR 4759 (reduced load)	Winchester	CCI 200	20.0	1695	<b>24.0</b>	2040

**WARNING:** Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

*Maximum loads should be used with CAUTION • C = Compressed Load*