



## 7-30 Waters

<b>.284"</b>	<b>7mm</b>
<b>Weight (grains)</b>	<b>TNT@ HP</b>
<b>Ballistic Coefficient</b>	110
<b>Sectional Density</b>	0.384
<b>COAL Tested</b>	0.195
<b>Speer Part No.</b>	2.710"
	1616

NOTE: Do not use pointed bullets in tubular magazines

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Alliant AR-Comp	Federal	Federal 210	34.4	2652	<b>37.4 C</b>	2863
Winchester 748	Federal	CCI 250	35.0	2503	<b>39.0 C</b>	2834
Alliant Power Pro Varmint	Federal	Federal 210	34.6	2662	<b>37.2</b>	2834
IMR 8208 XBR	Federal	Federal 210	33.2	2633	<b>36.2</b>	2828
Accurate 2015	Federal	CCI 200	29.0	2533	<b>33.0</b>	2767
Vitavuori N530	Federal	Federal 210	31.7	2580	<b>34.2</b>	2763
Alliant Reloder 15	Federal	CCI 200	33.0	2354	<b>37.0</b>	2757
Hodgdon H4895	Federal	CCI 200	32.0	2425	<b>36.0</b>	2739
Vihtavuori N135	Federal	CCI 200	31.0	2354	<b>35.0</b>	2735
Hodgdon H335	Federal	CCI 250	32.0	2498	<b>36.0</b>	2716
Hodgdon BL-C(2)	Federal	CCI 250	31.0	2432	<b>35.0</b>	2665
IMR 4895	Federal	CCI 200	30.5	2325	<b>34.5</b>	2655
Accurate 2230	Federal	CCI 250	27.5	2226	<b>31.5</b>	2642
IMR 3031	Federal	CCI 200	30.0	2228	<b>34.0</b>	2615

**WARNING:** Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load