



7mm-08 Remington

.284"	7mm Grand Slam® SP
Weight (grains)	175
Ballistic Coefficient	0.436
Sectional Density	0.310
COAL Tested	2.745"
Speer Part No.	1643

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Alliant Reloder 19	Remington	CCI 200	43.0	2396	47.0 C	2628
Alliant Power Pro 4000-MR	Federal	Federal 210	42.4 C	2407	46.2 C	2591
Alliant Reloder 16	Federal	Federal 210	40.3 C	2337	44.8 C	2576
Vihtavuori N165	Remington	CCI 200	43.0	2330	47.0 C	2575
Alliant Reloder 17	Federal	Federal 210	40.0	2297	44.2 C	2566
Alliant Power Pro 2000-MR	Federal	Federal 210	38.3	2298	42.4	2559
Ramshot Big Game	Federal	Federal 210	39.4	2366	43.6	2558
IMR 4350	Remington	CCI 200	40.0	2365	44.0	2542
Accurate 3100	Remington	CCI 200	43.0	2336	47.0 C	2536
Hodgdon H4350	Remington	CCI 200	40.0	2326	44.0 C	2507
Accurate 2520	Remington	CCI 250	35.0	2314	39.0	2502
IMR 4831	Remington	CCI 200	41.0	2240	45.0	2465
Hodgdon H4831SC	Remington	CCI 200	43.5	2355	45.5 C	2461
Winchester 760	Remington	CCI 250	41.0	2264	45.0	2461
Hodgdon H414	Remington	CCI 250	38.0	2208	42.0	2419
Hodgdon H380	Remington	CCI 250	38.0	2203	42.0	2408
Alliant Reloder 15	Remington	CCI 200	32.0	2153	36.0	2312

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load