



## 7mm Shooting Times Westerner

.284"	7mm Spitzer BTSP	7mm Spitzer SP Hot-Cor®	7mm Grand Slam® SP/CANN
Weight (grains)	160	160	160
Ballistic Coefficient	0.519	0.504	0.389
Sectional Density	0.283	0.283	0.283
COAL Tested	3.580"	3.600"	3.550"
Speer Part No.	1634	1635	1638

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Accurate 8700	Remington	CCI 250	87.0	3001	91.0 C	3133
Alliant Reloder 33	Federal	Federal 215	79.6	2767	88.4 C	3125
Alliant Reloder 50	Federal	Federal 215	79.0	2846	87.6 C	3105
IMR 7828	Remington	CCI 250	72.0	2954	76.0	3097
Accurate 3100	Remington	CCI 250	74.0	3020	76.0	3093
IMR 7977	Federal	Federal 215	74.3	2773	82.4	3087
Alliant Reloder 26	Federal	Federal 215	69.2	2775	76.7	3086
Alliant Reloder 25	Remington	CCI 250	71.0	2952	75.0	3076
Alliant Reloder 22	Remington	CCI 250	69.0	2947	73.0	3074
Hodgdon Retumbo	Federal	Federal 215	72.4	2810	79.2	3072
Alliant Reloder 23	Federal	Federal 215	67.7	2782	74.9	3050
IMR 4831	Remington	CCI 250	69.0	2967	71.0	3040
IMR 4350	Remington	CCI 250	65.5	2895	69.5	3033
Alliant Power Pro 4000-MR	Federal	Federal 215	64.9	2771	71.7	3027
Hodgdon H4831SC	Remington	CCI 250	66.0	2884	70.0	3019
Hodgdon H1000	Remington	CCI 250	75.0	2890	79.0	3010
Vihtavuori N170	Remington	CCI 250	72.0	2827	76.0	2955

**WARNING:** Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

*Maximum loads should be used with CAUTION • C = Compressed Load*