



## 8mm Remington Magnum

<b>.323"</b>	<b>8mm Spitzer SP Hot- Cor®</b>
<b>Weight (grains)</b>	150
<b>Ballistic Coefficient</b>	0.343
<b>Sectional Density</b>	0.205
<b>COAL Tested</b>	3.575"
<b>Speer Part No.</b>	2277

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
<b>IMR 4841</b>	Remington	CCI 250	80.0	3194	<b>86.0 C</b>	3436
<b>IMR 4350</b>	Remington	CCI 250	77.0	3158	<b>81.0</b>	3322
<b>Winchester 760</b>	Remington	CCI 250	76.0	3076	<b>80.0</b>	3225
<b>Hodgdon H380</b>	Remington	CCI 250	72.0	3038	<b>76.0</b>	3214
<b>Hodgdon H414</b>	Remington	CCI 250	74.0	3025	<b>78.0</b>	3191
<b>IMR 3031</b>	Remington	CCI 250	63.0	2969	<b>67.0</b>	3149
<b>IMR 4895</b>	Remington	CCI 250	62.0	2955	<b>66.0</b>	3134

**WARNING:** Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

*Maximum loads should be used with CAUTION • C = Compressed Load*