



9.3x74R

.366"	9.3mm
	Semi-Spitzer SP
	Hot-Cor®
Weight (grains)	270
Ballistic Coefficient	0.361
Sectional Density	0.288
COAL Tested	3.665"
Speer Part No.	2459

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Alliant Reloder 16	Norma	Federal 210	58.7	2238	64.4 C	2403
Winchester 760	Norma	Federal 210	58.7	2170	65.0	2382
IMR 4350	Norma	Federal 210	55.8	2149	61.8	2340
Alliant Reloder 15	Norma	Federal 210	51.0	2142	56.0	2322
IMR 4895	RWS	CCI 200	51.0	2097	55.0	2288
Hodgdon H380	Norma	Federal 210	53.4	2113	58.5	2281
IMR 4064	RWS	CCI 200	54.0	2157	58.0	2279
IMR 4451	Norma	Federal 210	55.5	2129	61.2	2272
IMR 4831	Norma	Federal 210	57.2	2070	63.2	2243
Winchester 748	RWS	CCI 200	56.0	2108	60.0	2235
Accurate 3100	RWS	CCI 200	60.0	1898	64.0 C	2086

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load